



# OPTIDRIVE™ CP<sup>2</sup>

AC Variable Speed Drive

## Powerful Performance

Advanced motor control



0.75kW – 250kW / 1HP – 350HP  
**200–600V** Single & 3 Phase Input

# Powerful Performance

World leading control for the latest generation of permanent magnet and standard induction motors

Manufacturing Pumping Conveyer Systems Machine Tools Processing Plants Chemical Rubber Elevators Cranes



## World Leading Motor Control

The all new Optidrive P2 offers the perfect combination of high performance together with ease of use to allow even the most demanding applications to be tackled easily.

Designed for fast installation and commissioning, Optidrive P2 provides the most cost effective solution for industry.

All Optidrive P2 units provide 150% overload for 60 seconds as standard, ensuring each drive is suitable for Heavy Duty applications, whilst the IP55 enclosed versions ensure the drive is tough enough to survive in industrial environments.

Extensive I/O and communications interface capabilities ensure the drive can be integrated quickly and efficiently into a wide variety of control systems with the minimum commissioning time, ensuring rapid start up. Invertertek's simple parameter structure, and carefully selected factory parameter settings ensure that commissioning time is kept to a minimum.



Compliant with international standards.  
Manufactured in the UK.

150% overload for 60 seconds



**IP20**

Panel mount units available up to 11kW



**IP55**

Wall mount units available up to 200kW



**IP66**

Wall mount units available up to 7.5kW

**Advanced Motor Control**

Optidrive P2 has been uniquely developed to allow a wide range of different motor types to be used, with only parameter changes being required. This technology allows the same drive to be used in a wide range of applications, allowing OEM's and end user alike to take advantage of the energy saving provided by using the latest motor technologies.

**AC Induction Motors**

The majority of AC motors in use today around the world are standard induction motors. These motors are relatively low cost, readily available and provide good performance with long service life. With the ever increasing focus on energy efficiency, motor manufacturers have refined and improved their designs in recent years.

Optidrive P2 has been developed to provide optimum control and maximum efficiency when operating with older motors designs, or newer high efficiency designs.

Operation can be in simple V/F control mode or in High Performance Third Generation Vector Mode, which provides up to 200% torque from zero speed without requiring an encoder.

**Permanent Magnet AC Motors**

Permanent magnet AC motors provide improved efficiency compared to standard induction motors. Using permanent magnets in the motor construction eliminates the need for any magnetising current, reducing electrical losses. PM motors have been used for many years in high performance applications, however this has always required the use of a feedback device, such as a resolver or encoder. Optidrive P2 has been designed to operate with AC PM motors without requiring any feedback device, allowing them to be used for their energy efficiency benefits without incurring extra cost and complexity in applications which do not require position feedback.

**Brushless DC Motors**

BLDC motors are similar to AC PM motors, however the design requires a slightly different control method to optimise the performance. Optidrive P2 has the flexibility to control this type of motor, requiring only simple parameter changes. This provides much greater flexibility for OEM's, allowing Optidrive P2 to be used in a variety of applications, with various motor types.

**Synchronous Reluctance Motors**

Synchronous Reluctance Motors (SynRM), not to be confused with Switched Reluctance Motors, share a similar stator construction to standard induction motors, however the rotor is substantially different, in order to improve the overall efficiency of the motor. SynRM motors are ideally suited to variable torque applications.

Optidrive P2 can control synchronous reluctance motors, allowing the energy saving benefits to be realised.

# At a Glance...

High performance, excellent usability and flexible to meet the needs of your application

**Keyhole  
Mounts for fast  
installation**




**Integrated  
Keypad & Display**  
(LED or Multi-language OLED  
Display)



**IP55 / NEMA 12**

**Integrated  
EMC Filter**



**Pluggable Control  
Terminals**



**High Quality  
Long-life Fans**

**Integral  
Brake  
Transistor**



**Integrated Cable  
Management**



Contactor-style Power Wiring Arrangement



Keyhole Mounts for fast installation



Convenient Reference Card

DIN Rail Mount

Modbus RTU and CANopen on board as standard



Modbus  
CANopen




Safe Torque Off (provided as standard)

Optidrive P2 features a safe torque off function to allow simple integration into machine critical safety circuits.


- Simple machine design reduces component costs, saves panel space and minimises installation time
- Faster shut down and reset procedures reduce system maintenance time
- Better safety standard compared to mechanical solution
- Better motor connection. Single cable with no interruption.



With



Without



# Applications

High performance, accurate motor control for even the most demanding of applications



## Mining & Quarrying

- Feed conveyers
- Crushers
- Cranes

## Metals & Processing

- Grinding
- Cutting
- Polishing
- Drilling
- Rolling

## Rubber & Plastics

- Extruders
- Moulding
- Mixers
- Winding

## Food & Beverage

- Conveyers
- Pumps
- Mixers
- Palletisers

Powerful, versatile and easy to use

## Cranes



### Requirements:

- High starting torque
- Smooth motor operation throughout starting and stopping phases
- Motor holding brake control
- Avoidance of load droop and sag
- Regeneration and braking capability during load lowering

### Optidrive P2 provides:

- Dedicated Hoist Mode Operation with motor holding brake control algorithm
- Up to 200% torque from zero speed in vector operation without encoder feedback
- Multiple Preset Speed or variable speed operation
- Built in dynamic braking transistor, requires only an external resistor

## Compressors



### Requirements:

- Precise regulation of speed to ensure a consistent end product
- High starting torque demand in many applications
- Maximum efficiency under all conditions
- Safe operation to prevent accidents and injuries

### Optidrive P2 Provides:

- PM Motor control mode to allow open loop operation with Permanent Magnet motors for maximum efficiency
- Maximum starting torque with standard AC motors
- Better than 0.5% speed holding accuracy in Open Loop Vector Operation
- Dedicated Safe Torque Off input complies with EN62061 SIL Level 2 for safe operation

## Winding



### Requirements:

- Precise control of motor torque over a broad speed range
- Accurate control of material tension under all conditions
- Open or closed loop control capability, based on tension feedback or winding diameter
- Web break protection in case of material breakage

### Optidrive P2 Provides:

- PID Closed Loop Tension Control with feedback from a load cell or dancer arm
- Open Loop Vector control provides optimum control of the output torque level
- Encoder feedback option allows for a very wide speed range, even down to zero speed
- Safe Torque Off input immediately disables the drive in Emergency conditions



# Options & Accessories

Installation options, plug-in modules and commissioning tools



## Fieldbus Interfaces

## Plug-in Options

Modbus RTU and CANopen on board as standard

For additional communication interfaces or functionality a range of plug-in modules is available:



**Profibus DP**  
OPT-2-PROFB-IN



**DeviceNet**  
OPT-2-DEVNT-IN



**Ethernet IP**  
OPT-2-ETHNT-IN



**Modbus TCP**  
OPT-2-MODIP-IN



**Profinet**  
OPT-2-PFNET-IN



**EtherCat**  
OPT-2-ETCAT-IN



### Encoder Feedback

**OPT-2-ENCOD-IN** (5 Volt)  
**OPT-2-ENCHT-IN** (15 – 30 Volt)

Closed loop encoder feedback, compatible with a wide range of incremental encoders

### Extended I/O

**OPT-2-EXTIO-IN**

- Additional 3 Digital Inputs
- Additional Relay Output

### Extended Relay

**OPT-2-CASCD-IN**

Additional 3 Relay Outputs:

- Relay 3** – Drive Healthy Indication
- Relay 4** – Drive Fault Indication
- Relay 5** – Drive Running Indication

Functions are programmable / adjustable



## Installation & Peripheral Options

A range of external EMC Filters, Brake Resistors, Input Chokes and Output Filters are available, to suit all installation requirements

### Optistick



#### Rapid Commissioning

- Allows rapid copying of parameters between multiple drives
- Provides Bluetooth wireless interface to a PC running OptiTools Studio
- Backup and restore of drive parameters

#### OPT-2-STICK-IN

## OptiTools Studio



## Powerful PC Software

### Drive commissioning and parameter backup

- Real-time parameter editing
- Drive network communication
- Parameter upload, download and storage
- Simple PLC function programming
- Real-time scope function and data logging
- Real-time data monitoring

Compatible with Windows XP, Windows Vista & Windows 7

kW	HP	Amps	Size	kW Model Code											HP Model Code										
				Product Family	Generation	Frame Size	Voltage Code	Power Rating Code	Supply Phases	Power Filter	EMC Filter	Enclosure	Display	PCB Coating	Product Family	Generation	Frame Size	Voltage Code	Power Rating Code	Supply Phases	Power Filter	EMC Filter	Enclosure	Display	PCB Coating
200-240V ± 10% 1 Phase Input	0.75	1	4.3	2	ODP	- 2 - 2	2	075	- 1	K	F	4	# - # N	ODP	- 2 - 2	2	010	- 1	H	F	4	# - # N			
	1.5	2	7	2	ODP	- 2 - 2	2	150	- 1	K	F	4	# - # N	ODP	- 2 - 2	2	020	- 1	H	F	4	# - # N			
	2.2	3	10.5	2	ODP	- 2 - 2	2	220	- 1	K	F	4	# - # N	ODP	- 2 - 2	2	030	- 1	H	F	4	# - # N			
200-240V ± 10% 3 Phase Input	0.75	1	4.3	2	ODP	- 2 - 2	2	075	- 3	K	F	4	# - # N	ODP	- 2 - 2	2	010	- 3	H	F	4	# - # N			
	1.5	2	7	2	ODP	- 2 - 2	2	150	- 3	K	F	4	# - # N	ODP	- 2 - 2	2	020	- 3	H	F	4	# - # N			
	2.2	3	10.5	2	ODP	- 2 - 2	2	220	- 3	K	F	4	# - # N	ODP	- 2 - 2	2	030	- 3	H	F	4	# - # N			
	4	5	15	3	ODP	- 2 - 3	2	040	- 3	K	F	4	# - # N	ODP	- 2 - 3	2	050	- 3	H	F	4	# - # N			
	5.5	7.5	24	3	ODP	- 2 - 3	2	055	- 3	K	F	4	2 - S N	ODP	- 2 - 3	2	075	- 3	H	F	4	2 - S N			
	5.5	7.5	24	4	ODP	- 2 - 4	2	055	- 3	K	F	4	N - T N	ODP	- 2 - 4	2	075	- 3	H	F	4	N - T N			
	7.5	10	30	4	ODP	- 2 - 4	2	075	- 3	K	F	4	N - T N	ODP	- 2 - 4	2	100	- 3	H	F	4	N - T N			
	11	15	46	4	ODP	- 2 - 4	2	110	- 3	K	F	4	N - T N	ODP	- 2 - 4	2	150	- 3	H	F	4	N - T N			
	15	20	60	5	ODP	- 2 - 5	2	150	- 3	K	F	4	N - T N	ODP	- 2 - 5	2	020	- 3	H	F	4	N - T N			
	18.5	25	72	5	ODP	- 2 - 5	2	185	- 3	K	F	4	N - T N	ODP	- 2 - 5	2	025	- 3	H	F	4	N - T N			
	22	30	90	6	ODP	- 2 - 6	2	022	- 3	K	F	4	N - T N	ODP	- 2 - 6	2	030	- 3	H	F	4	N - T N			
	30	40	110	6	ODP	- 2 - 6	2	030	- 3	K	F	4	N - T N	ODP	- 2 - 6	2	040	- 3	H	F	4	N - T N			
	37	50	150	6	ODP	- 2 - 6	2	037	- 3	K	F	4	N - T N	ODP	- 2 - 6	2	050	- 3	H	F	4	N - T N			
	45	60	180	6	ODP	- 2 - 6	2	045	- 3	K	F	4	N - T N	ODP	- 2 - 6	2	060	- 3	H	F	4	N - T N			
55	75	202	7	ODP	- 2 - 7	2	055	- 3	K	F	4	N - T N	ODP	- 2 - 7	2	075	- 3	H	F	4	N - T N				
75	100	248	7	ODP	- 2 - 7	2	075	- 3	K	F	4	N - T N	ODP	- 2 - 7	2	100	- 3	H	F	4	N - T N				
380-480V ± 10% 3 Phase Input	0.75	1	2.2	2	ODP	- 2 - 2	4	075	- 3	K	F	4	# - # N	ODP	- 2 - 2	4	010	- 3	H	F	4	# - # N			
	1.5	2	4.1	2	ODP	- 2 - 2	4	150	- 3	K	F	4	# - # N	ODP	- 2 - 2	4	020	- 3	H	F	4	# - # N			
	2.2	3	5.8	2	ODP	- 2 - 2	4	220	- 3	K	F	4	# - # N	ODP	- 2 - 2	4	030	- 3	H	F	4	# - # N			
	4	5	9.5	2	ODP	- 2 - 2	4	400	- 3	K	F	4	# - # N	ODP	- 2 - 2	4	050	- 3	H	F	4	# - # N			
	5.5	7.5	14	3	ODP	- 2 - 3	4	055	- 3	K	F	4	# - # N	ODP	- 2 - 3	4	075	- 3	H	F	4	# - # N			
	7.5	10	18	3	ODP	- 2 - 3	4	075	- 3	K	F	4	# - # N	ODP	- 2 - 3	4	100	- 3	H	F	4	# - # N			
	11	15	24	3	ODP	- 2 - 3	4	110	- 3	K	F	4	2 - S N	ODP	- 2 - 3	4	150	- 3	H	F	4	2 - S N			
	11	15	24	4	ODP	- 2 - 4	4	110	- 3	K	F	4	N - T N	ODP	- 2 - 4	4	150	- 3	H	F	4	N - T N			
	15	20	30	4	ODP	- 2 - 4	4	150	- 3	K	F	4	N - T N	ODP	- 2 - 4	4	200	- 3	H	F	4	N - T N			
	18.5	25	39	4	ODP	- 2 - 4	4	185	- 3	K	F	4	N - T N	ODP	- 2 - 4	4	250	- 3	H	F	4	N - T N			
	22	30	46	4	ODP	- 2 - 4	4	220	- 3	K	F	4	N - T N	ODP	- 2 - 4	4	300	- 3	H	F	4	N - T N			
	30	40	61	5	ODP	- 2 - 5	4	300	- 3	K	F	4	N - T N	ODP	- 2 - 5	4	040	- 3	H	F	4	N - T N			
	37	50	72	5	ODP	- 2 - 5	4	370	- 3	K	F	4	N - T N	ODP	- 2 - 5	4	050	- 3	H	F	4	N - T N			
	45	60	90	6	ODP	- 2 - 6	4	045	- 3	K	F	4	N - T N	ODP	- 2 - 6	4	060	- 3	H	F	4	N - T N			
	55	75	110	6	ODP	- 2 - 6	4	055	- 3	K	F	4	N - T N	ODP	- 2 - 6	4	075	- 3	H	F	4	N - T N			
	75	100	150	6	ODP	- 2 - 6	4	075	- 3	K	F	4	N - T N	ODP	- 2 - 6	4	100	- 3	H	F	4	N - T N			
	90	150	180	6	ODP	- 2 - 6	4	090	- 3	K	F	4	N - T N	ODP	- 2 - 6	4	150	- 3	H	F	4	N - T N			
110	175	202	7	ODP	- 2 - 7	4	110	- 3	K	F	4	N - T N	ODP	- 2 - 7	4	175	- 3	H	F	4	N - T N				
132	200	240	7	ODP	- 2 - 7	4	132	- 3	K	F	4	N - T N	ODP	- 2 - 7	4	200	- 3	H	F	4	N - T N				
160	250	302	7	ODP	- 2 - 7	4	160	- 3	K	F	4	N - T N	ODP	- 2 - 7	4	250	- 3	H	F	4	N - T N				
200	300	370	8	ODP	- 2 - 8	4	200	- 3	K	F	4	2 - T N	ODP	- 2 - 8	4	300	- 3	H	F	4	2 - T N				
250	350	450	8	ODP	- 2 - 8	4	250	- 3	K	F	4	2 - T N	ODP	- 2 - 8	4	350	- 3	H	F	4	2 - T N				
480-525V ± 10% 3 Phase Input	132	-	185	7	ODP	- 2 - 7	5	132	- 3	K	0	4	N - T N								N/A				
	150	-	205	7	ODP	- 2 - 7	5	150	- 3	K	0	4	N - T N									N/A			
	185	-	255	7	ODP	- 2 - 7	5	185	- 3	K	0	4	N - T N									N/A			
	200	-	275	7	ODP	- 2 - 7	5	200	- 3	K	0	4	N - T N									N/A			
500-600V ± 10% 3 Phase Input	0.75	1	2.1	2	ODP	- 2 - 2	6	075	- 3	K	0	4	# - # N	ODP	- 2 - 2	6	010	- 3	H	0	4	# - # N			
	1.5	2	3.1	2	ODP	- 2 - 2	6	150	- 3	K	0	4	# - # N	ODP	- 2 - 2	6	020	- 3	H	0	4	# - # N			
	2.2	3	4.1	2	ODP	- 2 - 2	6	220	- 3	K	0	4	# - # N	ODP	- 2 - 2	6	030	- 3	H	0	4	# - # N			
	4	5	6.5	2	ODP	- 2 - 2	6	400	- 3	K	0	4	# - # N	ODP	- 2 - 2	6	050	- 3	H	0	4	# - # N			
	5.5	7.5	9	2	ODP	- 2 - 2	6	055	- 3	K	0	4	# - # N	ODP	- 2 - 2	6	075	- 3	H	0	4	# - # N			
	7.5	10	12	3	ODP	- 2 - 3	6	075	- 3	K	0	4	# - # N	ODP	- 2 - 3	6	100	- 3	H	0	4	# - # N			
	11	15	17	3	ODP	- 2 - 3	6	110	- 3	K	0	4	# - # N	ODP	- 2 - 3	6	150	- 3	H	0	4	# - # N			
	15	20	22	3	ODP	- 2 - 3	6	150	- 3	K	0	4	2 - S N	ODP	- 2 - 3	6	200	- 3	H	0	4	2 - S N			
	15	20	22	4	ODP	- 2 - 4	6	150	- 3	K	0	4	N - T N	ODP	- 2 - 4	6	200	- 3	H	0	4	N - T N			
	18.5	25	28	4	ODP	- 2 - 4	6	185	- 3	K	0	4	N - T N	ODP	- 2 - 4	6	250	- 3	H	0	4	N - T N			
	22	30	34	4	ODP	- 2 - 4	6	220	- 3	K	0	4	N - T N	ODP	- 2 - 4	6	300	- 3	H	0	4	N - T N			
	30	40	43	4	ODP	- 2 - 5	6	300	- 3	K	0	4	N - T N	ODP	- 2 - 5	6	400	- 3	H	0	4	N - T N			
	37	50	54	5	ODP	- 2 - 5	6	370	- 3	K	0	4	N - T N	ODP	- 2 - 5	6	050	- 3	H	0	4	N - T N			
	45	60	65	5	ODP	- 2 - 5	6	045	- 3	K	0	4	N - T N	ODP	- 2 - 5	6	060	- 3	H	0	4	N - T N			
	55	75	78	6	ODP	- 2 - 6	6	055	- 3	K	0	4	N - T N	ODP	- 2 - 6	6	075	- 3	H	0	4	N - T N			
	75	100	105	6	ODP	- 2 - 6	6	075	- 3	K	0	4	N - T N	ODP	- 2 - 6	6	100	- 3	H	0	4	N - T N			
	90	125	130	6	ODP	- 2 - 6	6	090	- 3	K	0	4	N - T N	ODP	- 2 - 6	6	125	- 3	H	0	4	N - T N			
110	150	150	6	ODP	- 2 - 6	6	110	- 3	K	0	4	N - T N	ODP	- 2 - 6	6	150	- 3	H	0	4	N - T N				

### Enclosure & Display Types

Replace #s in model code with colour-coded option

- 2-SN**  **IP20** LED Display
- X-TN**  **IP66** Non-switched OLED Display
- Y-TN**  **IP66** Switched OLED Display
- 2-SN**  **IP20** LED Display
- N-TN**  **IP55** OLED Display
- 2-TN**  **IP20** OLED Display

**kW Models: Factory Settings**  
 Motor Rated Frequency: 50Hz  
 Motor Rated Voltage: 400V


**HP Models: Factory Settings**

## Drive Specification


Input Ratings	Supply Voltage	200 – 240V ± 10% 380 – 480V ± 10% 500 – 600V ± 10%	
	Supply Frequency	48 – 62Hz	
	Displacement Power Factor	> 0.98	
	Phase Imbalance	3% Maximum allowed	
	Inrush Current	< rated current	
	Power Cycles	120 per hour maximum, evenly spaced	
Output Ratings	Output Power	230V 1Ph. Input: 0.75–2.2kW (1–3HP) 230V 3Ph. Input: 0.75–75kW (1–100HP) 400V 3Ph. Input: 0.75–250kW 460V 3Ph. Input: 1–350HP 575V 3Ph. Input: 0.75–110kW (1–120HP)	
	Overload Capacity	150% for 60 seconds	
	Output Frequency	0 – 500Hz, 0.1Hz resolution	
	Typical Efficiency	> 98%	
	Ambient Conditions	Temperature	Storage: –40 to 60°C Operating: –10 to 50°C
	Altitude	Up to 1000m ASL without derating Up to 2000m maximum UL Approved Up to 4000m maximum (non UL)	
Humidity	95% Max, non condensing		
Vibration	Conforms to IEC 60068-2-6 Sinusoidal Vibration 10 - 57Hz @ 0.075mm Pk 57 - 150Hz @ 1g Pk		
Enclosure	Ingress Protection	IP20, IP55, IP66	
Programming	Keypad	Built-in keypad as standard Optional remote mountable keypad	
	Display	Built-in multi language OLED (IP55 & IP66) 7 Segment LED (IP20)	
	PC	OptiTools Studio	
Control Specification	Control Method	V/F Voltage Vector Energy Optimised V/F 3GV Sensorless Vector Speed Control 3GV Sensorless Vector Torque Control Closed Loop [Encoder] Speed Control Closed Loop [Encoder] Torque Control PM Vector Control BLDC Control Synchronous Reluctance	
	PWM Frequency	4–32kHz Effective	
	Stopping Mode	Ramp to Stop: User Adjustable 0.01–600 secs Coast to Stop	
	Braking	Motor Flux Braking Built-in Braking Transistor	
	Skip Frequency	Single point, user adjustable	
	Setpoint Control	Analog Signal	0 to 10 Volts 10 to 0 Volts –10 to +10 Volts 0 to 20mA 20 to 0mA 4 to 20mA 20 to 4mA
		Digital	Motorised Potentiometer (Keypad) Modbus RTU CANopen

Fieldbus Connectivity	Builtin	CANopen 125 – 1000kpbs Modbus RTU 9.6 - 115.2 kbps selectable 8N1, 8N2, 8E1, 8O1
	Optional	Other PROFIBUS DP (DPV1) PROFINET IO DeviceNet EtherNet/IP EtherCAT Modbus TCP
I/O Specification	Power Supply	24 Volt DC, 100mA, Short Circuit Protected 10 Volt DC, 5mA for Potentiometer
	Programmable Inputs	5 Total as standard (Optional additional 3) 3 Digital (Optional additional 3) 2 Analog / Digital Selectable
	Digital Inputs	8 – 30 Volt DC, internal or external supply Response time < 4ms Resolution: 12 bits Response time: < 4ms Accuracy: < 1% full scale Parameter adjustable scaling and offset
	Analog Inputs	4 Total (Optional additional 3) 2 Analog / Digital 2 Relays (Optional additional 3)
	Relay Outputs	Maximum Voltage: 250 VAC, 30 VDC Switching Current Capacity: 6A AC, 5A DC
	Analog Outputs	0 to 10 Volt 0 to 20mA 4 to 20mA
	Application Features	PID Control Internal PID Controller Multi Setpoint Select Standby / Sleep Mode Boost Function  Hoist Mode Dedicated Hoist Mode Motor Holding Brake Pre-Torque & Control Over Limit Protection
Maintenance & Diagnostics	Fault Memory	Last 4 Trips stored with time stamp
	Data Logging	Logging of data prior to trip for diagnostic purposes: Output Current Drive Temperature DC Bus Voltage
	Maintenance Indicator	Maintenance Indicator with user adjustable maintenance interval Onboard service life monitoring
	Monitoring	Hours Run Meter Resettable & Non Resettable kWh meters Cooling Fan Run Time
Standards Compliance	Low Voltage Directive	Adjustable speed electrical power drive systems. EMC requirements.
	EMC Directive	2004/108/EC 230V 1Ph. Filtered Units: Cat C1 According to EN61800-3:2004 400V 3Ph. Units: Cat C2 According to EN61800-3:2004
	Machinery Directive	2006/42/EC
	Conformance	CE, UL, C-Tick, EAC
	Marine	DNV Certified

## Model Code Guide



## Connection Diagram



NOT TO SCALE



Size	IP20		IP66		IP55			IP20
	2	3	2	3	4	5	6	8
mm Height	221	261	257	310	450	540	865	995
mm Width	110	131	188	211	171	235	330	482
mm Depth	185	205	239	266	252	270	330	480
kg Weight	1.8	3.5	4.8	7.7	11.5	23	55	200